



DOCK LEVELER STANDARD + OPTIONAL FEATURES

LEVELER TYPE: _____ **QUANTITY:** _____

- Mechanical (30-50k)
- Hydraulic (30-120k)

MODEL SIZE:

6-6	6-8	6-10	6-12
66-6	66-8	66-10	66-12
7-6	7-8	7-10	7-12

PIT STYLE

Curb Angle	Pit Kit
Pour-in-Place Pan:	
With Bottom (4-Sided)	Without Bottom (3-Sided)

Pit Width: _____

Pit Length: _____

Pit Depth Front: _____ Pit Depth Rear: _____

NOTE: Please complete the **Existing Pit Type Dock Leveler Pit Detail Form** for docks 10' or longer.

DOCK LEVELER OPTIONS:

- Full Range Operating Toe Guards (Mechanical Docks Only)
- Remote Power Pack (25' Hoses)
- 3 Wheel Deck Bracing
- Brush Weather Seal (3 Sides)
- Foam Insulation Under Deck
- Temporary Power Leads

PAINT AND FINISH:

- Grey Black Blue
- Custom Colour (Specify Code): _____
- Hot Dipped Galvanized
- Non-Skid Grit Surface on Lip and Deck

CAPACITY: (I-Beam starts at 40k lb.)

30,000 lb.	45,000 lb.	80,000 lb.
35,000 lb.	50,000 lb.	100,000 lb.
40,000 lb.	60,000 lb.	120,000 lb.

LIP SIZE:

16"	18"	20"
Tapered Lip (7' Wide Only)		
6" Safety Barrier Lip (Overall Length):		
22"	24"	26"

VOLTAGE:

115V / 1PH	460V / 3PH
208V / 1PH	575V / 3PH
208V / 3PH	Other: _____

CONTROL PANEL OPTIONS:

- Single Push Button Control (Standard)
- 3 Button Control (Dock Raise, Independent Lip Control, E-Stop)
- Single Button Control (c/w Door Interlock)

MOULDED RUBBER BUMPERS:

DB1013	DB1018
Other: _____	

LAMINATED RUBBER BUMPERS:

LB410-14	LB610-14	Other: _____
LVB420-11	LVB620-11	_____
Angle Both Sides (Standard)	P1 (Angle 1 Side)	P2 (Flat Bar - Both Sides)
Steel Faced		

Date:	Client:
Company:	Project:
Authorized By:	Authorized Signature:
Purchase Order #	

FOR INTERNAL USE ONLY
DATE RECEIVED: _____